



Garage

Y450101
 Y471190
 Y451300
 Y451500
 Y451000
 Y444000
 Y444100

Engine stand

400 kg. (880 lbs.) 360° rotating head. Robot welding and powder coating guarantee optimum lifetime in tough conditions.

Model	Cap.	Height	Width	Length	G.W.	N.W.
Y450101	400 kg	825	175	275	24,5	23

Car Dolly Heavy Duty

320-660 mm. range. Long rollers suitable for wide base tires.

Model	Cap.	Height	Width	Length	G.W.	N.W.
Y471190	680 kg	-	-	-	-	22



High lift transmission jacks

All models have a chrome main ram and hold-to-run control safety system. The wide base provides optimum stability and the efficient pump system ensures fast and precise reach of the load.

Model	Cap.	Min h.	Max h.	G.W.	N.W.
Y451300	300 kg	1150	1960	32	30
Y451500	500 kg	1150	1960	34	32
Y451000	1000 kg	1150	1960	48	46

Adaptor (Y451500-ADAP)

Special adaptor suitable for 300 kg (660 lbs.) and 500 kg (1100 lbs.) transmission jacks.

Auto body repair kits

Extension tubes snap together in seconds and fit perfectly without any tolerance. Chrome main rams guarantee optimum lifetime. Includes popular hydraulic ram spreader. Repairs dents and creases in tight places. Attachments push, pull, and lift.

Model	Cap.	G.W.	N.W.
Y444000	4 t	21	17
Y444100	10 t	39	31



Support

Y452300
 Y452600
 Y450301
 Y451600
 Y451200

Car Stand Set With Rubber Head

Pin type support axle stands adjust to multiple height positions. Large support saddle with oil resistant rubber adaptor for optimal stability and damage free contact; Designed with wide feet for high standard of safety.

Model	Cap.	Min h.	Max h.	Width	G.W.	N.W.
Y452300	3 t	295	435	210	5,5	5,2
Y452600	6 t	370	575	300	12	11



Jack stands

All stands have a heavy duty robot welded frame, and a multi-position ductile ratchet bar. The quick adjustment mechanism securely locks into the right location. Includes counter-weighted pawl for safe securing.

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.
Y450301	3 t	268	425	190	170	7,5	7
Y451600	6 t	394	597	270	240	15,2	13,8
Y451200	12 t	440	710	310	260	27,1	26



Truck / Tractor

Y471105
 Y471180
 Y471120
 Y471130
 Y454000

Wheel dolly

Wheel dolly – roll, lift, twist, lower; • Easy installation and de-installation of truck wheel assemblies • 1 man control • Heavy-duty industrial bearings • 3 positions for rollers depending on size of wheel • Great tool for every service truck • Avoid damage to wheel bolts and expensive modern rims • For all wheels from 6,5 – 22,5"

Model	Cap.	G.W.	N.W.
Y471105	max 250 kg	12	11,2



Wheel Breaker Set (Y471180)

10 Ton Wheel Breaker set. This kit eliminates one of the most dangerous jobs within the tire service industry: **WHEEL REMOVAL!**

Universal Bead Breaker Set (Y471120)

Works on most single, two - and three piece tires/rims. G.W. 21.

OTR Bead Breaker (Y471130)

To be used on 5 piece rims 25" to 51". With pry bar / bead loosening pockets. G.W. 14.

Forklifter/Tractor jack

4/5 Tons. This jack implements 2 lifting points; the low saddle is appropriate for service on forklift trucks while the high saddle is convenient during tractor maintenance jobs. Professional universal joint release valve makes it possible to lower the jack with load very precisely and free of any risks.

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.
Y454000	4/5 t	65/420	415/765	790	240	47	45



Winntec: A team of highly experienced automotive professionals.

Our group was established in 2002 and since then increasingly growing world-wide. The current program consists of a wide and comprehensive collection of

- Hydraulic (air) jacks
- Pit jacks
- Axle stands
- Pumps
- Wheel breaker kits
- Bottle jacks
- Cranes

Our constant mission is to offer advanced quality products and service.

We focus on bringing innovative equipment for professional usage while pricing remains attractive. Together with our loyal customers, which are many well-known companies throughout the world, we are motivated to become one of the leading names in the world wide automotive industry.

The Winntec group has currently 3 fully owned high-tech factory facilities in China. We have sourcing offices in the Far East (Taipeh, Hong Kong, Shang Hai) and continental sales offices and warehouses in The Netherlands and USA. All products are in compliance with the latest product standards / directives.

A. Dubbelman, Managing director

Standard Jacks

Y420303
Y422500
Y420302
Y420225
Y411350
Y420205

Turbo Lifter garage jack (Y420303)

3 Tons. This jack is equipped with the TURBO LIFTER system, rubber saddle and handle bumper. The professional universal joint release valve makes it possible to lower the jack with load very precisely and free of any risks. The pump pistons (protected with jacket to prevent from intrusion of dirt) are placed at a 45° angle so a complete pumping stroke will always be utilized. The jack has a chrome main ram.

Low profile garage jack (Y422500)

2.5 Tons. This Ultra low garage jack has a minimum height of 85 mm (3.35") and is equipped with a rubber saddle and handle bumper.

Economy jack (Y420302)

3 Tons. Economy model with single pump.

Turbo Lifter low profile long chassis jack (Y420225)

2.25 Tons. This long chassis ultra low garage jack is equipped with the TURBO LIFTER system, nylon wheels, rubber saddle and handle bumper. With a minimum height of 90 mm, a maximum height of 515 mm and a heavy duty frame this is the ideal jack for any tyre service shop.

Aluminium Garage Jack (Y411350)

1350 kg. This ultra light jack is equipped with rubber saddle and nylon wheels. The professional universal joint makes it possible to lower the jack with load very precisely and free of any risk. The pump piston is placed at a 45° angle so a complete pumping stroke will always be utilized.

Garage Jack with T-handle and foot pedal (Y420205)

2 Tons equipped with T-handle and foot paddle, professional universal joint.

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.
Y420303	3 t	130	490	720	360	43	41
Y422500	2,5 t	85	465	780	390	48,5	47
Y420302	3 t	130	490	720	360	41	39
Y420225	2,25 t	90	515	850	400	56	54
Y411350	1,35 t	80	380	500	240	11	10
Y420205	2 t	130	480	750	370	41	39



Bottle Jacks

Y410200
Y410400
Y410600
Y410800
Y411200
Y411500
Y412000
Y412001
Y413000

These professional bottle jacks meet the highest standards. All models have a chrome main ram and a chrome pump piston. The extension screws have a pressed thread. These units can be used horizontally and vertically.

Model	Cap.	Min H.	Lifting H.	Adjust H.	Max H.	N.W.
Y410200	2 t	158	90	60	308	2,3
Y410400	4 t	180	110	60	350	3,3
Y410600	6 t	197	125	60	382	4,4
Y410800	8 t	205	125	60	390	5,4
Y411200	12 t	214	125	60	399	7,2
Y411500	15 t	225	140	60	425	8,3
Y412000	20 t	244	145	60	449	10,5
Y412001	20 t short	190	90	60	340	9
Y413000	30 t	285	180	0	465	14,6



Industrial

Y418005
Y418010
Y418025
Y4781106
Y4781107
Y4781155
Y471150

Toejack

Truly a universal tool! The hydraulic toe jacks can do a wide variety of jobs faster & safer than standard jacks. With toe heights starting at 25mm and capacities up to 25 tons, Winntec hydraulic toe jacks are the first choice for transformer maintenance, heavy hauling, structural moving, and rigging.

Model	Cap.	Foot	Head	N.W.
Y418005	5 t	25-230	368-573	26
Y418010	10 t	30-260	420-650	36
Y418025	25 t	58-273	505-720	109

Industrial Cylinders

Industrial Cylinders, standard and flat body.

Model	Cap.	Foot	Head	N.W.
Y4781106	10 t	90	116	1,8
Y4781107	10 t	43	54	1,5



Industrial Single speed hand pump (Y4781155)

1000 cc, 700 bar.

Aluminum Air/Hydr. foot pump (Y471150)

2000 cc, 700 bar.



Pneumatic Jacks

Y432020
Y432003
Y432001

Air/manual bottle jack

20 Tons. This unit includes a welded base to prolong service. Chrome main ram and aluminium air motor guarantee optimum lifetime. Air filter, connected to hose, included. Y432003 comes on trolley.

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.
Y432020	20 t	245	470	130	220	17,3	16,5
Y432003	20 t	255	480	420	150	27	25,7

Air service jack

20 Tons. This heavy duty model is designed for servicing jobs in the truck industry. This jack has an extension screw in addition to 3 saddles that can be placed on top of each other for added height. Chrome main ram and aluminium air motor guarantee optimum lifetime. Air filter, connected to hose, included.

Model	Cap.	Min h.	Max h.	Hydr. Stroke	Ext. Screw	Length	Width	G.W.	N.W.
Y432001	20 t	185	373	108	80	580	320	51	47



Shop

Y440101
Y440103
Y461501

Foldable engine crane

This 1 Ton crane constructed from heavy-gauge, welded square tubular steel, includes the following features:

- Hold-to-run control safety system • Nylon wheels • Ram and pump are combined into one unit to eliminate hoses and/or connections
- 4 positions to secure arm • Chrome ram • Rear wheels rotate 360° • Safety feet at base to support stability when crane is folded up
- Max. lifting height 1940 mm (76.4")

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.
Y440101	1 t	300	1940	1300	900	84	80
Y440103	1 t	470	1865	1500	900	91	83

Extra features Y440103

- Steel wheels covered with heavy duty rubber • Professional hook with bearing • Pump rotates 180° for one man operation
- Ready-to-use model (no assembly required)

Workshop press European model

15 Tons. This press comes standard with two-speed pump, arbor plates and pressure gauge. Welded ready-to-use model. Nine different height positions for securing the table. Chrome main ram and pump pistons.

Model	Cap.	Frame H.	Frame W.	Hydr. Stroke	Table pos.	G.W.	N.W.
Y461501	15 t	1730	740	195	9	159	131



Long Reach Jacks

Y420200
Y420301
Y420500
Y421000
Y420510
Y421010

Long chassis jacks

All models are equipped with a foot pedal and ergonomically designed handle. These jacks have a chrome main ram and professional universal joint release valve that makes it possible to lower loads very precisely and free of any risks.

Model	Cap.	Min h.	Max h.	Length	Width	G.W.	N.W.	
Y420200	2 t	140	800	1250	470	65	58	
Y420301	3 t	130	600	1305	320	75	66	
Y420500	5 t	150	685	1420	355	115	95	
Y421000	10 t	160	685	1700	510	170	145	
Y420510	*Y420510	5 t	150	685	1420	355	115	95
Y421010	*Y421010	10 t	160	685	1700	510	170	145

*Air/Manual models

